

## Colour Stains

Our colour stains use our hardwax oil ingredient as base to colour your wood surface and treat at the same time. This is an eco-friendly product made from natural plant material and free from solvents. It is easy to apply drying in less than 8 hours – 4 hours in ideal conditions – and does not need sanding in between coats. It is also less nauseous than other products. The product is applied directly onto the wood surface and allowed to dry. To deepen the colour you can add more coats. The colour stain needs to be sealed with a final coat our hardwax oil.

Available in variety of colours: pearl white; medium oak and burnt oak.



### Features:

- Suitable for all wood surface - floors, doors, kitchen tops, furniture
- Eco-friendly finishes
- No sanding between coats: requires only one sanding
- Ingredients contains natural plant and bees wax
- Quick drying -2 coats can be applied in just 4 hours (in suitable conditions)
- Does not peel or flake
- Dirt-resistant: dirt and dust can be removed easily
- Resistant to substances such as fizzy drinks, coffee, wine, beer, etc Complies with DIN 68861-1B
- Sweat and saliva proof. Complies with DIN 53160
- Damaged areas can be touched up with virtually no visible brush marks
- Available in silk (matt), satin or gloss and in a range of colours

### Safety Instructions:

Flammable. Keep out of the reach of children. Repeated exposure may cause skin dryness or cracking. Use only in well ventilated areas. Trial area recommended.

### Application:

#### Preparing the Floor/Surface

- Sand the surface with appropriate grit sandpaper(80-150)
- Clean and remove all dust and dirt
- Provide adequate warmth and good ventilation (coldness and humidity will slow down drying)

#### Usage:

- Apply the Hardwax Oil thinly and evenly with a roller or brush allowing approx 30g per m2, removing any excess with a scraper
- Any excess should be removed with a piece of non-woven material (e.g fleece)
- The surface will dry in 4 – 8 hours
- Apply a second coat (optional but recommended). Allow to dry thoroughly overnight - the floor may then be used
- The surface will reach maximum hardness after 24 hours

#### Cleaning & Maintenance

- Regularly remove loose dust and dirt using a broom or vacuum cleaner
- Mop the surface using a cleaner such as Christina Meyer's 2 in 1

#### Cleaner and Wax Treatment

- Use a damp mop never a wet one
- For heavier soiling increase the frequency of cleaning and amount of 2 in 1 Cleaner used

#### Repairing damaged areas

- Sand the damaged area lightly in stages starting with 150 to 220 grit paper
- Then follow the instructions given in the section application